Science. Applied to Life.™

3M Separation and Purification Sciences Division Specification Sheet

3M[™] CTG-Klean Encapsulated Filter System GPJ Series

3M[™] CTG-Klean Encapsulated Filter System GPJ Series is a completely enclosed filtration system that uses a separate pressure vessel and disposable filter pack to isolate the product to be filtered from the housing. This design reduces the extensive time and labour involved with filter change-outs and cleaning of conventional housings.

Environmental concerns and operator exposure to product and cleaning solvents can be reduced. The streamlined system, coupled with high performance, long-life filters, make GPJ Series the clear choice for safe, environmentally friendly and cost-effective filtration.

This series contains a filter cartridge in a transparent soft capsule. It can be used for the filtration of various compatible fluids with 3M filters.

Applications:

- Chemicals
- Battery Manufacturing (e.g., Li-ion Battery)
- Cathode/Anode/Electrolytes Filtration
- Paints and Coatings
- Inks
- Adhesives

Filter System Features:

Contactless approach	Reduced odours	Product recovery	See-through design		
Easy, fast and clean	Operator's safety	Compressible package reducing waste	Transparent package visual inspection		
Cleaning time is shortened, reduced process cycle time.	Exposure to volatile organic compounds is reduced to a minimum due to a sealed operating system.	Lower risk of environmental contamination, less waste of product.	Minimize risk of spillage.		



3M[™] Betapure[™] AU Series

3M[™] Betapure[™] AU Series are made from bi-component fibres with polypropylene core and polyethylene sheath. The outcome of this construction is a rigid structure that resists fibre migration and pore size change over a wide range of differential pressure offering great benefits in filtrations applications needing particle screening. The Betapure AU series is available in nominal ratings of 75, 100 and 150 µm in 1GPJ encapsulated format.

3M[™] Betapure[™] NT-T Series


The all-polypropylene filter is constructed using a design that utilizes flow enhancing filter media and an innovative flow pattern. The result is an absolute-rated filter with high on-stream life for cost-effective filtration over conventional melt-blown filter technologies. The 3M[™] Betapure[™] NT-T Series was designed to provide significantly superior service life while maintaining a consistent filtration efficiency. This filter design is available in absolute filtration rating of 1, 2, 3, 5, 10, 20, 40, 50 and 70 µm.


3M[™] Betapure[™] SKYL Series


Non-woven polypropylene depth filters provide filtration efficiency as well as high flow rates and offered in two nominal micron ratings of 0.5 and 1.0 micron. This filter design offer all polypropylene components for applications which are compatible with polypropylene. These applications include where clarification or classification is the filtration objective needing low extractables.


3M[™] Micro-Klean[™] RT Series


3M[™] Micro-Klean[™] RT Series provide cost effective depth filtration combined with high surface area provided with machined upstream surface grooves. This design provides continuous bonding from downstream surface to upstream surface, eliminating the risk of layering during operation as the pressure drop increases. The Micro-Klean RT Series are available in 1, 5, 10, 25, 50 and 75 µm nominal ratings.


















Filter System Design:

There are several designs to fit various applications. If the presence of air bubbles in the filtrates is a concern, the design with vent option is more appropriate.



Specifications:	
Cartridge Length	10 in (25.4 cm) and 20 in (50.8 cm)
Head	Polyolefin
Bag Layers	Outside Nylon and Inside (Wetted Surface) Polyethylene
Vent	HDPE
O-Ring	EPDM
Check valve parts (ball)	Polypropylene
Valve parts (Spring)	304 Stainless Steel
Maximum Use Temperature	104°F (40°C)
Maximum Operation Pressure	0.5 MPa @ 104°F (40°C)

3M[™] CTG-Klean Encapsulated Filter System GPJ Series Ordering Guide

Table 1: 3M[™] CTG-Klean Encapsulated Filter System 1GPJ Series

Media Type	Model No	3M ID	SAP ID	Materials Description	Grade (µm)	Length (in/cm)	Check Valve	Air Vent
	1GPJ1AUQN1	XA-0064-7996-9	7100292770	3M [™] Betapure [™] AU Series Filter Cartridge 1GPJ1AUQN1 CTG 1×1 75UM	75	10/25.4	ball	Yes
	1GPJ2AUQN1	XA-0064-7993-6	7100292736	3M [™] Betapure [™] AU Series Filter Cartridge 1GPJ2AUQN1 CTG 1×2 75UM	75	20/50.8	ball	Yes
2M™ Dotonuro™ All	1GPJ1AUVN1	XA-0064-7994-4	7100292769	3M [™] Betapure [™] AU Series Filter Cartridge 1GPJ1AUVN1 CTG 1×1 100UM	100	10/25.4	ball	Yes
Media Type 3M [™] Betapure [™] AU 3M [™] Micro-Klean [™] RT 3M [™] Betapure [™] NT-T	1GPJ2AUVN1	XA-0064-7995-1	7100292737	3M [™] Betapure [™] AU Series Filter Cartridge 1GPJ2AUVN1 CTG 1×2 100UM	100	20/50.8	ball	Yes
	1GPJ1AUWN1	XA-0064-7992-8	7100292772	3M [™] Betapure [™] AU Series Filter Cartridge 1GPJ1AUWN1 CTG 1×1 150UM	(µm)(µ/m)7510/25.7520/50.10010/25.10010/25.10010/25.10015010/25.1015010/25.10110/25.10120/50.10520/50.10520/50.10520/50.10520/50.10520/50.101020/50.102510/25.M2520/50.M2520/50.M5010/25.M5010/25.M5010/25.M7520/50.M7520/50.M7520/50.M220/50.M220/50.M310/25.M520/50.M520/50.M520/50.M520/50.M520/50.M520/50.M520/50.M620/50.M520/50.M520/50.M520/50.M520/50.M520/50.M520/50.M520/50.M520/50.M520/50.M520/50.M520/50. <td>10/25.4</td> <td>ball</td> <td>Yes</td>	10/25.4	ball	Yes
	1GPJ2AUWN1	XA-0064-7991-0	7100292771	3M [™] Betapure [™] AU Series Filter Cartridge 1GPJ2AUWN1 CTG 1×2 150UM	150	20/50.8	ball	Yes
	1GPJ1RTYN0	XA-0064-7998-5	7100291967	3M [™] Micro-Klean [™] RT Series Filter Cartridge 1GPJ1RTYN0 CTG 1X1 1UM	1	10/25.4	ValveIballba	No
	1GPJ2RTYN0	XA-0064-8077-7	7100292017	3M [™] Micro-Klean [™] RT Series Filter Cartridge 1GPJ2RTYN0 CTG 1X2 1UM	1	20/50.8	ball	No
	1GPJ1RTBN0	XA-0064-7988-6	7100291936	3M [™] Micro-Klean [™] RT Series Filter Cartridge 1GPJ1RTBN0 CTG 1X1 5UM	5	10/25.4	ball	No
	1GPJ2RTBN0	XA-0064-7987-8	7100292014	3M [™] Micro-Klean [™] RT Series Filter Cartridge 1GPJ2RTBN0 CTG 1X2 5UM	5	20/50.8	ball	No
	1GPJ2RTBS0	XA-0064-7990-2	7100291935	3M [™] Micro-Klean [™] RT Series Filter Cartridge 1GPJ2RTBS0 CTG 1X2 5UM	5	20/50.8		No
	1GPJ2RTBS1	XA-0064-7989-4	7100291966	3M [™] Micro-Klean [™] RT Series Filter Cartridge 1GPJ2RTBS1 CTG 1X2 5UM	5	20/50.8		Yes
	1GPJ1RTCN0	XA-0064-7986-0	7100291865	3M [™] Micro-Klean [™] RT Series Filter Cartridge 1GPJ1RTCN0 CTG 1X1 10UM	10	10/25.4	ball	No
	1GPJ2RTCN0	XA-0064-7985-2	7100292015	3M [™] Micro-Klean [™] RT Series Filter Cartridge 1GPJ2RTCN0 CTG 1X2 10UM	10	20/50.8	ball	No
3M [™] Micro-Klean [™] RT	1GPJ1RTFN1	XA-0064-8078-5	7100292501	3M [™] Micro-Klean [™] RT Series Filter Cartridge 1GPJ1RTFN1 CTG 1X1 25UM	25	10/25.4	ball	Yes
	1GPJ1RTFN0	XA-0064-8079-3	7100292500	3M [™] Micro-Klean [™] RT Series Filter Cartridge 1GPJ1RTFN0 CTG 1X1 25UM	25	10/25.4	ball	No
	1GPJ2RTFN0	XA-0064-8081-9	7100292502	3M [™] Micro-Klean [™] RT Series Filter Cartridge 1GPJ2RTFN0 CTG 1X2 25UM	25	20/50.8	ball	No
	1GPJ1RTLN0	XA-0064-8082-7	7100292763	3M [™] Micro-Klean [™] RT Series Filter Cartridge 1GPJ1RTLN0 CTG 1X1 50UM	50	10/25.4	ball	No
	1GPJ2RTLN0	XA-0064-8083-5	7100292764	3M [™] Micro-Klean [™] RT Series Filter Cartridge 1GPJ2RTLN0 CTG 1X2 50UM	50	20/50.8	ball	No
	1GPJ1RTQN1	XA-0064-8084-3	7100292765	3M™ Micro-Klean™ RT Series Filter Cartridge 1GPJ1RTQN1 CTG 1X1 75UM	75	10/25.4	ball	Yes
3M [™] Micro-Klean [™] RT	1GPJ1RTQN0	XA-0064-8076-9	7100292766	3M™ Micro-Klean™ RT Series Filter Cartridge 1GPJ1RTQN0 CTG 1X1 75UM	75	10/25.4	ball	No
	1GPJ2RTQN1	XA-0064-8075-1	7100292767	3M™ Micro-Klean™ RT Series Filter Cartridge 1GPJ2RTQN1 CTG 1X2 75UM	75	20/50.8	ball	Yes
	1GPJ2RTQN0	XA-0064-7999-3	7100292768	3M™ Micro-Klean™ RT Series Filter Cartridge 1GPJ2RTQN0 CTG 1X2 75UM	75	20/50.8	ball	No
		10/25.4	ball	No				
	1GPJ1NTT020N0	JN-7220-3862-5	7010692605	3M [™] Betapure [™] NTT Series Filter Cartridge 1GPJ1NTT020N0 LF CTG 1X1 2UM	2	10/25.4	ball	No
	1GPJ2NTT020N0	JN-7220-3866-6	7010692606	3M [™] Betapure [™] NTT Series Filter Cartridge 1GPJ2NTT020N0 LF CTG 1X2 2UM	2	20/50.8	ball	No
	1GPJ1NTT030N0	JN-7220-3863-3	7100279605	3M [™] Betapure [™] NTT Series Filter Cartridge 1GPJ1NTT030N0 LF CTG 1X1 3UM	3	10/25.4	ball	No
	1GPJ1NTT050N0	UU-0119-0244-0	7100279320	3M [™] Betapure [™] NTT Series Filter Cartridge 1GPJ1NTT050N0 LF CTG 1X1 5UM	5	10/25.4	ball	No
	1GPJ2NTT050N0	UU-0117-6763-7	7100273143	3M [™] Betapure [™] NTT Series Filter Cartridge 1GPJ2NTT050N0 LF CTG 1X2 5UM	5	20/50.8	ball	No
	1GPJ1NTT100N0	UU-0117-7947-5	7100273368	3M [™] Betapure [™] NTT Series Filter Cartridge 1GPJ1NTT100N0 LF CTG 1X1 10UM	10	10/25.4	ball	No
	1GPJ2NTT100N0	UU-0117-6762-9	7100273142	3M [™] Betapure [™] NTT Series Filter Cartridge 1GPJ2NTT100N0 LF CTG 1X2 10UM	10	20/50.8	ball	No
3M™ Betapure™ NT-T	1GPJ1NTT200N0	UU-0117-7946-7	7100273367	3M [™] Betapure [™] NTT Series Filter Cartridge 1GPJ1NTT200N0 LF CTG 1X1 20UM	20	10/25.4	ball	No
	1GPJ2NTT200N0	UU-0117-6761-1	7100273141	3M [™] Betapure [™] NTT Series Filter Cartridge 1GPJ2NTT200N0 LF CTG 1X2 20UM	20	20/50.8	ball	No
	1GPJ1NTT400N0	JN-7220-3386-5	7100279606	3M [™] Betapure [™] NTT Series Filter Cartridge 1GPJ1NTT400N0 LF CTG 1X1 40UM	40	10/25.4	ball	No
	1GPJ2NTT400N0	JN-7220-3388-1	7010692488	3M™ Betapure™ NTT Series Filter Cartridge 1GPJ2NTT400N0 LF CTG 1X2 40UM	40	20/50.8	ball	No
	1GPJ1NTT500N0	UU-0117-7117-5	7100276484	3M [™] Betapure [™] NTT Series Filter Cartridge 1GPJ1NTT500N0 LF CTG 1X1 50UM	50	10/25.4	ball	No
	1GPJ2NTT500N0	JN-7220-3870-8	7100279610	3M [™] Betapure [™] NTT Series Filter Cartridge 1GPJ2NTT500N0 LF CTG 1X2 50UM	50	20/50.8	ball	No
	1GPJ2NTT500N1	UU-0119-0245-7	7100279321	3M [™] Betapure [™] NTT Series Filter Cartridge 1GPJ2NTT500N1 LF CTG 1X2 50UM	50	20/50.8	ball	Yes
	1GPJ1NTT700N0	JN-7220-3527-4	7100279607	3M [™] Betapure [™] NTT Series Filter Cartridge 1GPJ1NTT700N0 LF CTG 1X1 70UM	70	10/25.4	ball	No
	1GPJ2NTT700N0	JN-7220-3871-6	7010692607	3M [™] Betapure [™] NTT Series Filter Cartridge 1GPJ2NTT700N0 LF CTG 1X2 70UM	70	20/50.8	ball	No
	1GPJ2SKYL0050S0	JN-7220-3297-4	7010692468	3M™ Betapure™ SKYL Series Filter Cartridge 1GPJ2SKYL0050S0 CTG 1X2 0.5UM	0.5	20/50.8	ball with SS spring	No
3M [™] Betapure [™] SKYL	1GPJ2SKYL0100S0	JN-7220-3140-6	7010692437	3M [™] Betapure [™] SKYL Series Filter Cartridge 1GPJ2SKYL0100S0 CTG 1X2 1UM	1	20/50.8	ball with SS spring	No

3M[™] CTG-Klean Encapsulated Filter System GPJ Series Housing:

When using 3M[™] CTG-Klean Encapsulated Filter System GPJ Series Capsules, please use the dedicated housing. Please contact a 3M representative for more details on housings.





Model Number	3M ID	SAP ID	Inlet/Outlet Fittings	Housing Material	Design Pressure (Mpa/psi)	Cartridge Size	Cartridge Vent	Housing Weight (Kg/lb)	Opening and Closing Method
C1-J1-SZ	UU-0125-1669-4	7100303706	1.5 in (3.8 cm) Sanitary/ Tri-Clover	004.00	0.5 /72	1 × 10 in (25.4 cm)	No	5/11	C-Clamp
C1-J1-SVZ	UU-0125-1513-4	7100303708					Yes		
C1-J2-SZ	UU-0125-1670-2	7100303705		304 SS		1 × 20 in (50.8 cm)	No	7 / 45 4	
C1-J2-SVZ	UU-0125-1514-2	7100303707					Yes	7 / 15.4	

Intended Use and Product Selection: 3M[™] CTG-Klean Encapsulated Filter Systems GPJ Series are intended for use in industrial filtration applications of aqueous fluids in accordance with the applicable product instructions and specifications. 3M CTG-Klean Encapsulated Filter Systems GPJ Series products are also intended for use with non-aqueous fluids where materials of construction are compatible. Since there are many factors that can affect a product's use, the customer and user remain responsible for determining whether the 3M product is suitable and appropriate for the user's specific application, including user conducting an appropriate risk assessment and evaluating the 3M product in user's application.

Restrictions on Use: 3M advises against the use of these 3M products in any application other than the stated intended use(s) since other applications have not been evaluated by 3M and may result in an unsafe or unintended condition. Do not use in any manner whereby the 3M product, or any extractable or leachable from the 3M product, may become part of or remains in a medical device, drug, cosmetic, supplement, infant formula; or in applications involving life-sustaining medical applications or prolonged contact with internal bodily fluids or tissues. 3M CTG-Klean Encapsulated Filter Systems GPJ Series products are not for use in food contact applications.

Technical Information: The technical information, guidance, and other statements contained in this document or otherwise provided by 3M are based upon records, tests, or experience that 3M believes to be reliable, but the accuracy, completeness, and representative nature of such information is not guaranteed. Such information is intended for people with knowledge and technical skills sufficient to assess and apply their own informed judgment to the information. No license under any 3M or third party intellectual property rights is granted or implied with this information.

Product Selection and Use: Many factors beyond 3Ms control and uniquely within users knowledge and control can affect the use and performance of a 3M product in a particular application. As a result, customer is solely responsible for evaluating the product and determining whether it is appropriate and suitable for customers application, including conducting a workplace hazard assessment and reviewing all applicable regulations and standards (e.g., OSHA, ANSI, etc.). Failure to properly evaluate, select, and use a 3M product and appropriate safety products, or to meet all applicable safety regulations, may result in injury, sickness, death, and/or harm to property.

Warranty, Limited Remedy, and Disclaimer: Unless a different warranty is specifically stated on the applicable 3M product packaging or product literature (in which case such warranty governs), 3M warrants that each 3M product meets the applicable 3M product specification at the time 3M ships the product. 3M MAKES NO OTHER WARRANTIES OR CONDITIONS, EXPRESS OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OR CONDITION OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE, OR ARISING OUT OF A COURSE OF DEALING, CUSTOM, OR USAGE OF TRADE. If a 3M product does not conform to this warranty, then the sole and exclusive remedy is, at 3M's option, replacement of the 3M product or refund of the purchase price.

Limitation of Liability: Except for the limited remedy stated above, and except to the extent prohibited by law, 3M will not be liable for any loss or damage arising from or related to the 3M product, whether direct, indirect, special, incidental, or consequential (including, but not limited to, lost profits or business opportunity), regardless of the legal or equitable theory asserted, including, but not limited to, warranty, contract, negligence, or strict liability.



3M Separation and Purification Sciences Division 3M Canada 300 Tartan Drive London, Ontario N5V 4M9 Canada 1-800-443-1661

3M, 3M Science. Applied to Life., Betapure and Micro-Klean are trademarks of 3M. Used under license in Canada. © 2023, 3M. All rights reserved. All other trademarks are the property of their respective owners. 2306-26545 E